



普傑國際股份有限公司

PROFESSOR TECHNOLOGY CO., LTD.

## PRODUCT SPECIFICATION

### 產品承認書

Customer: \_\_\_\_\_

Product Name: **5.1 Channel Surround Headphone.**

Model No: **CP5.1-GAME**

Production Region: **China**

Version: **English**

Customer Approval Stamp.

Date: \_\_\_ / \_\_\_ / \_\_\_.

Contact Info: Jimmy Chan  
+886-3-4551081 ext:209  
jimmychan@professor.com.tw  
jack@professor.com.tw

Model No:

CP5.1-GAME

Date:

30/Nov/2004

Checked by:

Approved by:

**PROFESSOR TECHNOLOGY CO., LTD.**

5F, No.25-1, JiLin Rd., Chung-Li Industrial Park, Taoyuan 320, Taiwan.

TEL :+886-3-4551081 FAX :+886-3-4553913

## Cosmetic List 外觀圖清單



### Power Supply



1. Headphone
2. Control Box (Processor) with Volume control.
3. RCA Plug (right)
4. RCA Plug (Left)
5. DC Jack




1. Double-side RCA Jack (red)
2. Double-side RCA Jack (white)


## Specification 規格

Part	Description	Qty.
1.	Driver Front: 27mm Dynamic Speaker 32 Ohm 150mW Rear: 27mm Dynamic Speaker 32 Ohm 150mW Center: 27mm Dynamic Speaker 32 Ohm 100mW Bass: 30mm Dynamic Speaker 24 Ohm 15mW	2 2 2 2
2.	Processor Input: AC100~240V 50/60Hz ; Euro type Plug Output: DC+5V 1A	1
3.	Headphone type Closed Air type.	
4.	Cable & Connector Cord Length: 240 cm Connector: Rca plug (right) red color. Rca plug (left) white color. Accessories : Double-side Rca Jack (white) Double-side Rca Jack (red)	1 1 1 1
5.	Weight Gross Weight: 700 g (include accessories and package) Net Weight: 465 g (only headphone)	
6.	Package type Blister	
7.	Power Supply Input: AC100~240V 50/60Hz ; Euro type Plug Output: DC+5V 1A DC plug: OD=5.5mm ID=2.7mm	


# Circuit Diagram

## 電路圖





Title		TDA2022M AMPLIFIER FOR CENTER & BASS	
Size	Number	Revision	
A4	NO.2		
Date:		1-30-2004	
Drawn By:		SHEEPER/SCHLDR	
Sheet of		4	




Title		FRONT & REAR AMPLIFIER	
Size	Number	NO:3	Revision
A4			
DATE:	1 Dec 2011	SWR: J1	
FILE:	F:\PROGRAM FILES\PROFESSOR\PCB\DESIGN\PCB\PCB.DDB	DATE BY:	

## Acoustic Characteristic 音響特性


	Characteristic	Front Speaker	Rear Speaker	Center Speaker	Bass Speaker
1.	Frequency Range	20Hz~20kHz	20Hz~20kHz	20Hz~20kHz	20Hz~3kHz
2.	Sensitivity	97± 3dB	97± 3dB	97± 3dB	121± 3dB
3.	Speaker Type & Size	∅27mm Dynamic	∅27mm Dynamic	∅27mm Dynamic	∅30mm Dynamic
4.	Normal Impedance	32Ω	32Ω	32Ω	24Ω
5.	Output Power	150mW	150mW	100mW	15mW (max 100mW)

Speaker: **Center** Model: CP5.1 GAME  
Voltage applied for F.R. = 0.126V  
Measure distance: 0.01m




Speaker  
Frequency Response  
頻率響應圖

Speaker: Front & Rear      Model: CP5.1 GAME  
Voltage applied for F.R.: 0.178V  
Measure distance: 0.01m



Speaker: **Bass** Model: CP5.1 GAME  
Voltage applied for F.R.=0.155V  
Measure distance: 0.01m



## Electrical Characteristics 電氣特性

### Characteristic



1.	電源電壓 Supply Voltage	DC5V
2.	靜態消耗電流 Quiescent Drain Current	$\leq 0.1$ A
3.	最大消耗電流 Max Drain Current	$\leq 1.3$ A
4.	總諧波失真 Total Harmonic Distortion	$\leq 5\%$
5.	動態範圍 Dynamic Range	100dB
6.	平衡度 Channel Unbalance	$\geq 2$ dB
7.	分離度 Separation	$\leq 100$ dB
8.	信噪比 S/N	85dB
8.	阻尼係數 Damping Factor	20

**Packaging  
包裝**


FRONT VIEW




BACK VIEW



Side View



## Packaging Construction 包裝方法示意圖



# Carton Packaging Construction 外箱包裝

